

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

MIRS67-600 (M) G2 2500 HF TW M20 FR/PC



The Norwegian EPD Foundation

Owner of the declaration:

Glamox AS

Product:

MIRS67-600 (M) G2 2500 HF TW M20 FR/PC

Declared unit:

1 pcs

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR

IBU PCR - Part B for luminaires, lamps, and components for luminaires

Program operator:

The Norwegian EPD Foundation

Declaration number:

NEPD-6540-5798-EN

Registration number:

NEPD-6540-5798-EN

Issue date: 07.05.2024

Valid to: 07.05.2029

EPD software:

LCAno EPD generator ID: 281130

General information

Product

MIRS67-600 (M) G2 2500 HF TW M20 FR/PC

Program operator:

The Norwegian EPD Foundation
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-norge.no

Declaration number:

NEPD-6540-5798-EN

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
IBU PCR - Part B for luminaires, lamps, and components for
luminaires

Statement of liability:

The owner of the declaration shall be liable for the underlying
information and evidence. EPD Norway shall not be liable with respect
to manufacturer information, life cycle assessment data and
evidences.

Declared unit:

1 pcs MIRS67-600 (M) G2 2500 HF TW M20 FR/PC

Declared unit with option:

A1,A2,A3,A4,A5,B6,C1,C2,C3,C4,D

Functional unit:

1 pc MIR (M) manufactured in Glamox Molde. Transport to customer,
installed and used according to a specific lighting regime. Including
waste treatment in Europe at end-of-life.

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information
and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4.
Verification of each EPD is made according to EPD-Norway's
guidelines for verification and approval requiring that tools are i)
integrated into the company's environmental management system, ii)
the procedures for use of the EPD tool are approved by EPD-Norway,
and iii) the process is reviewed annually by an independent third
party verifier. See Appendix G of EPD-Norway's General Programme
Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data
and test-EPD in accordance with EPDNorway's procedures and
guidelines for verification and approval of EPD tools. Approval
number: NEPDT41.

Third party verifier:

Vito D'Incognito, Take Care International

(no signature required)

Owner of the declaration:

Glamox AS
Contact person: Birger Holo
Phone: +47 97551574
e-mail: birger.holo@glamox.com

Manufacturer:

Glamox AS
Birger Hatlebakks veg 15
6415 Molde, Norway

Place of production:

Glamox production site Molde (Norway)
Birger Hatlebakks veg 15
6415 Molde, Norway

Management system:

ISO 9001, ISO 14001; Molde: ATEX, ISO 80079-34 (IECEX), ISO45001,
ISO50001; Kirkenær: ISO 13485; Keila: ISO 45001, ISO 50001;
Dobczyce: ATEX, ISO 80079-34 (IECEX), Module D 2014/90/EU

Organisation no:

912007782

Issue date:

07.05.2024

Valid to:

07.05.2029

Year of study:

2023

Comparability:

EPD of construction products may not be comparable if they not
comply with EN 15804 and seen in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2021.09,
developed by LCA.no. The EPD tool is integrated in the company's
management system, and has been approved by EPD Norway.
NEPDT42

Developer of EPD: Marthe Øyen Gaasø

Reviewer of company-specific input data and EPD: Jonny A. Strømme

Approved:



Håkon Hauan
Managing Director of EPD-Norway

Product

Product description:

MIR G2 (Marine) is a high quality luminaire applicable for a wide range of different areas. They are designed to meet maritime requirements and has a wide variety of installation options, minimal maintenance and excellent overall economy. Due to the LED the luminaire is energy saving and offers a long lifetime. The luminaire housing is manufactured in acid-proof stainless steel with a white epoxy/polyester powder-coated finish. It's supplied with a self-extinguishing (V0) and diffuser in impact-proof frosted polycarbonate with a one-piece silicone-free gasket and clips in acid-proof steel.

This environmental product declaration can be used for the following luminaires:

MIR104296 - MIRS67-600 (M) G2 2500 HF 830 TW M20 FR/PC

MIR101985 - MIRS67-600 (M) G2 2500 HF 840 TW M20 FR/PC

MIR103735 - MIRS67-600 (M) G2 2500 HF 850 TW M20 FR/PC

Product specification

| Materials | kg | % |
|------------------------------------|-------------|---------------|
| Coating materials | 0,07 | 1,93 |
| Electronic - Auxiliaries | 0,00 | 0,01 |
| Electronic - Connector | 0,04 | 1,14 |
| Electronic - LED chip | 0,00 | 0,02 |
| Electronic - LED driver | 0,52 | 13,83 |
| Electronic - LED plate | 0,04 | 0,97 |
| Electronic - Wire | 0,13 | 3,48 |
| Metal - Brass | 0,03 | 0,70 |
| Metal - Stainless steel | 1,47 | 39,54 |
| Metal - Steel | 0,64 | 17,12 |
| Metal - Steel with aluzinc coating | 0,22 | 5,84 |
| Plastic - Polyamide | 0,05 | 1,24 |
| Plastic - Polycarbonate (PC) | 0,46 | 12,37 |
| Plastic - Polyurethane (PUR) | 0,06 | 1,67 |
| Rubber, synthetic | 0,01 | 0,13 |
| Total | 3,73 | 100,00 |

| Packaging | kg | % |
|--------------------------------|-------------|---------------|
| Packaging - Paper | 0,05 | 13,62 |
| Packaging - Recycled cardboard | 0,31 | 86,38 |
| Total incl. packaging | 4,08 | 100,00 |

Technical data:

Please visit the product page on our website for more technical information.

<https://www.glamox.com/global-marine/products>

Market:

Global

Reference service life, product

100 000 hours lifetime for the luminaire according to the technical qualities for the product family.

Reference service life, building or construction works

25 years. Standard service life for installation in Marine, Offshore and Wind.

LCA: Calculation rules

Declared unit:

1 pcs MIRS67-600 (M) G2 2500 HF TW M20 FR/PC

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) can be excluded. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.

| Materials | Source | Data quality | Year |
|------------------------------------|--|---|------|
| Coating materials | Ecoinvent 3.6 | Database | 2019 |
| Electronic - Auxiliaries | Modified ecoinvent 3.6 | Database | 2019 |
| Electronic - Connector | ecoinvent 3.6 | Database | 2019 |
| Electronic - LED chip | Scholand et al. (2012) + Ecoinvent 3.6 | Scientific literature + database | 2017 |
| Electronic - LED driver | Product composition + ecoinvent 3.6 | Supplier data + database | 2019 |
| Electronic - LED plate | ecoinvent 3.6 | Database | 2019 |
| Electronic - Wire | Material composition + ecoinvent 3.6 | Supplier data + database | 2019 |
| Metal - Brass | ecoinvent 3.6 | Database | 2019 |
| Metal - Stainless steel | ecoinvent 3.6 | Database | 2019 |
| Metal - Steel | ecoinvent 3.6 | Database | 2019 |
| Metal - Steel | SSAB | EPD (EN15804A1) + company dataset (EN15804A2) | 2020 |
| Metal - Steel with aluzinc coating | S-P-06909 | EPD | 2022 |
| Packaging - Paper | ecoinvent 3.6 | Database | 2019 |
| Packaging - Recycled cardboard | ecoinvent 3.6 | Database | 2019 |
| Plastic - Polyamide | ecoinvent 3.6 | Database | 2019 |
| Plastic - Polycarbonate (PC) | ecoinvent 3.6 | Database | 2019 |
| Plastic - Polyurethane (PUR) | ecoinvent 3.6 | Database | 2019 |
| Rubber, synthetic | ecoinvent 3.6 | Database | 2019 |

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

| Product stage | | | Construction installation stage | | Use stage | | | | | | | End of life stage | | | | Beyond the system boundaries |
|---------------|-----------|---------------|---------------------------------|----------|-----------|-------------|--------|-------------|---------------|------------------------|-----------------------|----------------------------|-----------|------------------|----------|------------------------------------|
| Raw materials | Transport | Manufacturing | Transport | Assembly | Use | Maintenance | Repair | Replacement | Refurbishment | Operational energy use | Operational water use | De-construction demolition | Transport | Waste processing | Disposal | Reuse-Recovery-Recycling-potential |
| A1 | A2 | A3 | A4 | A5 | B1 | B2 | B3 | B4 | B5 | B6 | B7 | C1 | C2 | C3 | C4 | D |
| X | X | X | X | X | MND | MND | MND | MND | MND | X | MND | X | X | X | X | X |

System boundary:


The analysis is a cradle-to-grave study of one luminaire manufactured and installed, used according to a specific lighting regime over a specific lifetime, including waste treatment at end-of-life.

A1-A5 includes the extraction and production of raw materials, transportation to the production site, the production process itself, transport to the market and assembly.

B6 is the operational energy use stage of the luminaire based on the the technical lifetime hours for the product family and the power consumption of the declared luminaire.

C1-C4 includes de-installation of the luminaire, average transport between location/application/installation site and waste treatment facility, waste processing and disposal in Europe. Waste treatment of the product follows the default values provided in EN 50693.

D shows the recyclability of metals and plastics and allows the producers a credit for the net scrap that is produced at the end of a product's life. The benefits from recycling of net scrap are described in formula from EN 15804:2012+A2:2019. Substitution of heat and electricity generated by the incineration with energy recovery of plastic insulation and other parts is also calculated in module D.



Additional technical information:

Please visit our website www.glamox.com for more technical information.

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Module A4:

Transport from manufacturing location in Molde to Glamox central warehouse in Poland (1755 km) + average distribution into the market (2000 km).

Module B6:

The operational energy use of the luminaire is calculated based on the methodology provided in IBU PCR Part B for luminaires, lamps, and components for luminaires. The energy consumption model for luminaire used in the PCR follows the application scenarios developed in EN 15193:2007. To calculate the electricity use of the luminaire, the following scenario parameters have been applied:

- Product family user scenario = Custom *
- Active power of the luminaire = 18 watt
- Passive power of the luminaire (Pp) = 0 watt
- Totally yearly time usage (tD+tN) = 5256 hours
- Standard year time (ty) = 8760 hours
- The occupancy dependency factor (FO) = 1 (factor, no unit)
- The dependency factor (FD) = 1 (factor, no unit)
- The product specific constant illuminance factor (FCP) = 1 (factor, no unit)
- The specific empiric lifetime of the luminaire in years (a) = 19,03 years **

*The custom user scenario has been developed by Glamox. This scenario is based on our long industry knowledge of the typical use of this product family and the technical lifetime for the luminaire.

**The application specific empiric lifetime is 25 years, but since the luminaire has a technical lifetime for 100 000 hours will the estimated 60 % usage yearly exceed this. We therefore use the lifetime hours divided by totally yearly time usage to find our empirical lifetime in this calculation for energy consumption.

Module C2:

Average transport to European waste treatment facilities (500km).

Modules C3 and C4:

Waste treatment of the product follows the default values provided in EN 50693, Product Category Rules for life cycle assessments of electronic and electrical products and systems, table G.4. This table specified how different types of raw materials used in A1 will likely be treated during the end-of-life of the product. Waste treatments in C3 include material recycling and incineration with and without energy recovery and fly ash extraction. Disposal in C4 consist of landfilling of different waste fractions and of ashes.

Module D:

The recyclability of metals, plastics, and electronic components allows the producers a credit for the net scrap that is produced at the end of a product's life. The benefits from recycling of net scrap are described in formula from EN 15804:2012+A2:2019. Substitution of heat and electricity generated by the incineration with energy recovery of plastic insulation and other parts is also calculated in module D.

The MOW business is of a global nature, that is why it is important to state that the EPD results for these stages are only valid when the products are being treated in Europe when reaching end of life.

| Transport from production place to user (A4) | Capacity utilisation (incl. return) % | Distance (km) | Fuel/Energy Consumption | Unit | Value (Liter/tonne) |
|--|---------------------------------------|---------------|-------------------------|-------|---------------------|
| Truck, 16-32 tonnes, EURO 6 (km) - Europe | 36,7 % | 3755 | 0,043 | l/tkm | 161,47 |
| Assembly (A5) | | Unit | Value | | |
| Waste, cardboard and paper, to average treatment - A5 including transport (kg) | kg | 0,05 | | | |
| Waste, packaging, corrugated board box, 40 % recycled, to average treatment (kg) - A5, inkl. 85 km transp. | kg | 0,31 | | | |
| Operational energy (B6) | | Unit | Value | | |
| Electricity, low voltage, HFO burned in generator, for ship and offshore electricity supply (kWh) - Global | kWh/DU | 1800,00 | | | |
| Transport to waste processing (C2) | Capacity utilisation (incl. return) % | Distance (km) | Fuel/Energy Consumption | Unit | Value (Liter/tonne) |
| Truck, 16-32 tonnes, EURO 6 (km) - Europe | 36,7 % | 500 | 0,043 | l/tkm | 21,50 |

| Waste processing (C3) | Unit | Value | | | |
|--|-------------|--------------|--|--|--|
| Brass to recycling (kg) | kg | 0,02 | | | |
| Copper to recycling (kg) | kg | 0,04 | | | |
| Steel to recycling (kg) | kg | 1,87 | | | |
| Waste treatment of hazardous waste, incineration with fly ash extraction (kg) | kg | 0,07 | | | |
| Waste treatment of non-hazardous waste, incineration with energy recovery and fly ash extraction (kg) | kg | 0,00 | | | |
| Waste treatment of plastic mixture, incineration with energy recovery and fly ash extraction (kg) | kg | 0,43 | | | |
| Waste treatment per kg electronics scrap from LED plate, without components, recycling of copper - C3 (kg) | kg | 0,02 | | | |
| Waste treatment per kg electronics scrap from PWB, with components, recycling of metals - C3 (kg) | kg | 0,17 | | | |
| Waste treatment per kg used electronic components, manual separation (kg) | kg | 0,69 | | | |
| Waste treatment per kg used PWB, shredding and separation - C3 (kg) | kg | 0,37 | | | |
| Disposal (C4) | Unit | Value | | | |
| Landfilling of ashes from incineration of Hazardous waste, process per kg ashes and residues - C4 (kg) | kg | 0,01 | | | |
| Landfilling of ashes from incineration of Non-hazardous waste, process per kg ashes and residues (kg) | kg | 0,00 | | | |
| Landfilling of ashes from incineration of Plastic mixture, process per kg ashes and residues (kg) | kg | 0,01 | | | |
| Landfilling of brass (kg) | kg | 0,01 | | | |
| Landfilling of copper (kg) | kg | 0,03 | | | |
| Landfilling of hazardous waste (kg) | kg | 0,19 | | | |
| Landfilling of non-hazardous waste (kg) | kg | 0,00 | | | |
| Landfilling of plastic mixture (kg) | kg | 0,43 | | | |
| Landfilling of steel (kg) | kg | 0,47 | | | |
| Benefits and loads beyond the system boundaries (D) | Unit | Value | | | |
| Substitution of copper with net scrap from PWB, without components (kg) | kg | 0,00 | | | |
| Substitution of electricity, in Norway (MJ) | MJ | 0,67 | | | |
| Substitution of primary brass with net scrap (kg) | kg | 0,00 | | | |
| Substitution of primary copper with net scrap (kg) | kg | 0,03 | | | |
| Substitution of primary metals with net scrap from PWB, with components (kg) | kg | 0,05 | | | |
| Substitution of primary steel with net scrap (kg) | kg | 1,46 | | | |
| Substitution of thermal energy, district heating, in Norway (MJ) | MJ | 10,21 | | | |

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

| Environmental impact | | | | | | | |
|--|------------------------|-----------|----------|----------|----------|----------|--|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | |
|  GWP-total | kg CO ₂ -eq | 5,66E+01 | 7,28E-01 | 2,71E-01 | 2,50E+00 | 6,07E-01 | |
|  GWP-fossil | kg CO ₂ -eq | 5,67E+01 | 7,28E-01 | 2,55E-01 | 2,50E+00 | 5,71E-03 | |
|  GWP-biogenic | kg CO ₂ -eq | -2,56E-01 | 2,93E-04 | 1,44E-02 | 1,04E-03 | 6,01E-01 | |
|  GWP-luluc | kg CO ₂ -eq | 7,79E-02 | 2,73E-04 | 7,26E-04 | 8,91E-04 | 1,89E-06 | |
|  ODP | kg CFC11 -eq | 3,55E-06 | 1,63E-07 | 1,79E-08 | 5,67E-07 | 1,21E-09 | |
|  AP | mol H+ -eq | 4,01E-01 | 3,70E-03 | 1,64E-03 | 7,19E-03 | 2,70E-05 | |
|  EP-FreshWater | kg P -eq | 5,73E-03 | 5,59E-06 | 1,27E-05 | 2,00E-05 | 4,69E-08 | |
|  EP-Marine | kg N -eq | 6,10E-02 | 8,22E-04 | 3,09E-04 | 1,42E-03 | 8,95E-06 | |
|  EP-Terrestrial | mol N -eq | 7,18E-01 | 9,17E-03 | 3,51E-03 | 1,59E-02 | 9,68E-05 | |
|  POCP | kg NMVOC -eq | 2,36E-01 | 2,90E-03 | 9,64E-04 | 6,10E-03 | 2,78E-05 | |
|  ADP-minerals&metals ¹ | kg Sb-eq | 1,19E-02 | 1,90E-05 | 1,25E-05 | 6,91E-05 | 1,39E-07 | |
|  ADP-fossil ¹ | MJ | 7,19E+02 | 1,09E+01 | 2,65E+00 | 3,78E+01 | 7,99E-02 | |
|  WDP ¹ | m ³ | 2,00E+03 | 9,99E+00 | 3,81E+02 | 3,66E+01 | 1,01E-01 | |

| Indicator | Unit | B6 | C1 | C2 | C3 | C4 | D |
|--|------------------------|----------|----------|----------|----------|----------|-----------|
|  GWP-total | kg CO ₂ -eq | 1,38E+03 | 0,00E+00 | 3,33E-01 | 1,36E+00 | 1,02E-01 | -4,55E+00 |
|  GWP-fossil | kg CO ₂ -eq | 1,38E+03 | 0,00E+00 | 3,33E-01 | 1,36E+00 | 1,02E-01 | -4,53E+00 |
|  GWP-biogenic | kg CO ₂ -eq | 2,40E-01 | 0,00E+00 | 1,38E-04 | 1,05E-03 | 1,74E-04 | -9,25E-03 |
|  GWP-luluc | kg CO ₂ -eq | 7,05E-02 | 0,00E+00 | 1,19E-04 | 4,37E-04 | 3,55E-04 | -6,91E-03 |
|  ODP | kg CFC11 -eq | 2,72E-04 | 0,00E+00 | 7,55E-08 | 3,17E-08 | 5,67E-09 | -4,31E-03 |
|  AP | mol H+ -eq | 1,25E+01 | 0,00E+00 | 9,58E-04 | 1,18E-03 | 2,87E-04 | -1,99E-01 |
|  EP-FreshWater | kg P -eq | 3,27E-03 | 0,00E+00 | 2,66E-06 | 9,90E-06 | 2,01E-06 | -1,17E-03 |
|  EP-Marine | kg N -eq | 1,50E+00 | 0,00E+00 | 1,89E-04 | 2,85E-04 | 1,24E-04 | -1,14E-02 |
|  EP-Terrestrial | mol N -eq | 1,65E+01 | 0,00E+00 | 2,12E-03 | 3,11E-03 | 7,96E-04 | -1,51E-01 |
|  POCP | kg NMVOC -eq | 4,89E+00 | 0,00E+00 | 8,12E-04 | 8,34E-04 | 3,19E-04 | -4,62E-02 |
|  ADP-minerals&metals ¹ | kg Sb-eq | 9,86E-04 | 0,00E+00 | 9,20E-06 | 2,02E-06 | 3,27E-07 | -4,40E-03 |
|  ADP-fossil ¹ | MJ | 1,70E+04 | 0,00E+00 | 5,04E+00 | 2,62E+00 | 7,30E-01 | -5,17E+01 |
|  WDP ¹ | m ³ | 7,29E+03 | 0,00E+00 | 4,87E+00 | 2,07E+01 | 6,20E+00 | -7,68E+00 |

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

A luminaire is a product that consumes energy during the use phase. Combined with a relatively long expected lifetime and the environmental impact of generating electricity, the use phase (B6) will normally be the most contributing stage to the overall environmental impact of the declared unit. It is important to be aware that the actual calculations of the effect of B6 is particularly sensitive to which use scenario and fuel source that is chosen.

| Additional environmental impact indicators | | | | | | | |
|---|---------------------|-------------------|----------|----------|----------|----------|----------|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | |
|  | PM | Disease incidence | 3,21E-06 | 4,27E-08 | 1,81E-08 | 1,53E-07 | 3,99E-10 |
|  | IRP ² | kgBq U235 -eq | 2,42E+00 | 4,75E-02 | 4,12E-02 | 1,65E-01 | 3,42E-04 |
|  | ETP-fw ¹ | CTUe | 3,40E+03 | 7,94E+00 | 1,11E+01 | 2,80E+01 | 1,07E-01 |
|  | HTP-c ¹ | CTUh | 1,84E-07 | 0,00E+00 | 5,52E-10 | 0,00E+00 | 3,00E-12 |
|  | HTP-nc ¹ | CTUh | 2,47E-06 | 8,74E-09 | 1,24E-08 | 3,06E-08 | 1,34E-10 |
|  | SQP ¹ | dimensionless | 2,70E+02 | 7,21E+00 | 1,48E+00 | 2,65E+01 | 5,36E-02 |

| Indicator | Unit | B6 | C1 | C2 | C3 | C4 | D | |
|---|---------------------|-------------------|----------|----------|----------|----------|----------|-----------|
|  | PM | Disease incidence | 9,39E-05 | 0,00E+00 | 2,04E-08 | 9,58E-09 | 5,11E-09 | -5,40E-07 |
|  | IRP ² | kgBq U235 -eq | 7,36E+01 | 0,00E+00 | 2,20E-02 | 1,26E-02 | 2,40E-03 | -1,36E-01 |
|  | ETP-fw ¹ | CTUe | 8,38E+03 | 0,00E+00 | 3,73E+00 | 8,62E+00 | 3,14E+02 | -1,48E+03 |
|  | HTP-c ¹ | CTUh | 4,99E-07 | 0,00E+00 | 0,00E+00 | 3,07E-09 | 1,97E-10 | -1,54E-08 |
|  | HTP-nc ¹ | CTUh | 4,34E-06 | 0,00E+00 | 4,08E-09 | 1,72E-07 | 1,73E-09 | -3,97E-07 |
|  | SQP ¹ | dimensionless | 2,08E+03 | 0,00E+00 | 3,52E+00 | 7,29E-01 | 1,85E+00 | -3,49E+01 |

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Potential Soil Quality Index (dimensionless)

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

| Resource use | | | | | | | |
|---|-------|----------------|----------|----------|----------|----------|-----------|
| Indicator | | Unit | A1 | A2 | A3 | A4 | A5 |
|  | PERE | MJ | 8,88E+01 | 1,50E-01 | 2,83E+01 | 5,42E-01 | 1,32E-03 |
|  | PERM | MJ | 4,31E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | -5,47E+00 |
|  | PERT | MJ | 9,31E+01 | 1,50E-01 | 2,83E+01 | 5,42E-01 | -5,46E+00 |
|  | PENRE | MJ | 7,07E+02 | 1,09E+01 | 2,65E+00 | 3,78E+01 | 7,99E-02 |
|  | PENRM | MJ | 2,46E+01 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
|  | PENRT | MJ | 7,20E+02 | 1,09E+01 | 2,65E+00 | 3,78E+01 | 7,99E-02 |
|  | SM | kg | 7,88E-01 | 0,00E+00 | 6,92E-03 | 0,00E+00 | 0,00E+00 |
|  | RSF | MJ | 1,64E+00 | 5,33E-03 | 2,30E-02 | 1,94E-02 | 4,36E-05 |
|  | NRSF | MJ | 1,76E+00 | 1,87E-02 | 6,17E-02 | 6,93E-02 | 1,80E-04 |
|  | FW | m ³ | 5,42E-01 | 1,12E-03 | 2,13E-01 | 4,05E-03 | 3,77E-05 |

| Indicator | | Unit | B6 | C1 | C2 | C3 | C4 | D |
|---|-------|----------------|----------|----------|----------|-----------|----------|-----------|
|  | PERE | MJ | 4,91E+01 | 0,00E+00 | 7,21E-02 | 3,78E-01 | 1,85E-01 | -1,00E+01 |
|  | PERM | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
|  | PERT | MJ | 4,91E+01 | 0,00E+00 | 7,21E-02 | 3,78E-01 | 1,85E-01 | -1,00E+01 |
|  | PENRE | MJ | 1,70E+04 | 0,00E+00 | 5,04E+00 | 2,62E+00 | 7,30E-01 | -5,17E+01 |
|  | PENRM | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | -2,86E+01 | 0,00E+00 | 0,00E+00 |
|  | PENRT | MJ | 1,70E+04 | 0,00E+00 | 5,04E+00 | -2,60E+01 | 7,30E-01 | -5,17E+01 |
|  | SM | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 4,02E-03 | 1,97E-02 |
|  | RSF | MJ | 1,26E+00 | 0,00E+00 | 2,58E-03 | 7,04E-03 | 9,67E-04 | 5,88E-02 |
|  | NRSF | MJ | 5,24E+00 | 0,00E+00 | 9,22E-03 | -1,71E-04 | 3,56E-02 | 1,39E+00 |
|  | FW | m ³ | 1,01E+02 | 0,00E+00 | 5,39E-04 | 3,03E-03 | 6,26E-04 | -3,80E-02 |

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0*10⁻³ = 0,009"

*INA Indicator Not Assessed

| End of life - Waste | | | | | | | |
|---|------|------|----------|----------|----------|----------|----------|
| Indicator | | Unit | A1 | A2 | A3 | A4 | A5 |
|  | HWD | kg | 4,04E-01 | 5,53E-04 | 4,52E-02 | 1,95E-03 | 0,00E+00 |
|  | NHWD | kg | 1,52E+01 | 4,97E-01 | 7,47E-01 | 1,84E+00 | 3,53E-01 |
|  | RWD | kg | 2,50E-03 | 7,42E-05 | 2,10E-05 | 2,58E-04 | 0,00E+00 |

| Indicator | | Unit | B6 | C1 | C2 | C3 | C4 | D |
|---|------|------|----------|----------|----------|----------|----------|-----------|
|  | HWD | kg | 2,22E+00 | 0,00E+00 | 2,60E-04 | 8,41E-05 | 2,06E-01 | -1,93E-02 |
|  | NHWD | kg | 1,31E+01 | 0,00E+00 | 2,45E-01 | 1,86E-01 | 9,55E-01 | -1,18E+00 |
|  | RWD | kg | 1,21E-01 | 0,00E+00 | 3,43E-05 | 4,19E-06 | 1,82E-06 | -1,18E-04 |

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3}$ = 0,009"

*INA Indicator Not Assessed

| End of life - Output flow | | | | | | | |
|---|-----|------|----------|----------|----------|----------|----------|
| Indicator | | Unit | A1 | A2 | A3 | A4 | A5 |
|  | CRU | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
|  | MFR | kg | 0,00E+00 | 0,00E+00 | 6,66E-01 | 0,00E+00 | 3,28E-01 |
|  | MER | kg | 0,00E+00 | 0,00E+00 | 1,26E-01 | 0,00E+00 | 2,47E-02 |
|  | EEE | MJ | 0,00E+00 | 0,00E+00 | 7,70E-02 | 0,00E+00 | 2,02E-02 |
|  | EET | MJ | 0,00E+00 | 0,00E+00 | 1,17E+00 | 0,00E+00 | 3,06E-01 |

| Indicator | | Unit | B6 | C1 | C2 | C3 | C4 | D |
|---|-----|------|----------|----------|----------|----------|----------|-----------|
|  | CRU | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 | 0,00E+00 |
|  | MFR | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 1,93E+00 | 3,84E-05 | -9,95E-04 |
|  | MER | kg | 0,00E+00 | 0,00E+00 | 0,00E+00 | 5,00E-01 | 9,38E-07 | -1,29E-04 |
|  | EEE | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 6,57E-01 | 6,09E-05 | -3,96E-04 |
|  | EET | MJ | 0,00E+00 | 0,00E+00 | 0,00E+00 | 9,94E+00 | 9,21E-04 | -5,99E-03 |

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

*Reading example: 9,0 E-03 = $9,0 \cdot 10^{-3}$ = 0,009"

*INA Indicator Not Assessed

| Biogenic Carbon Content | | |
|---|------|---------------------|
| Indicator | Unit | At the factory gate |
| Biogenic carbon content in product | kg C | 1,41E-01 |
| Biogenic carbon content in accompanying packaging | kg C | 2,28E-02 |

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

| Electricity mix | Source | Amount | Unit |
|---------------------------|---------------|--------|---------------------------|
| Electricity, Norway (kWh) | ecoinvent 3.6 | 24,33 | g CO ₂ -eq/kWh |

Dangerous substances

The product contains no substances on the REACH Candidate list at or above 100 ppm, 0,01 % by weight.

Indoor environment

Not relevant.

Additional Environmental Information

| Additional environmental impact indicators required in NPCR Part A for construction products | | | | | | | |
|--|------------------------|----------|----------|----------|----------|----------|-----------|
| Indicator | Unit | A1 | A2 | A3 | A4 | A5 | |
| GWPIOBC | kg CO ₂ -eq | 5,71E+01 | 7,28E-01 | 2,63E-01 | 2,50E+00 | 5,71E-03 | |
| Indicator | Unit | B6 | C1 | C2 | C3 | C4 | D |
| GWPIOBC | kg CO ₂ -eq | 1,38E+03 | 0,00E+00 | 3,33E-01 | 1,36E+00 | 1,05E-01 | -5,31E+00 |

GWPIOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Bibliography

ISO 14025:2010. Environmental labels and declarations - Type III environmental declarations - Principles and procedures. International Organization for Standardization.

ISO 14044:2006. Environmental management - Life cycle assessment - Requirements and guidelines. International Organization for Standardization.

EN 15804:2012+A2:2019. Environmental product declaration - Core rules for the product category of construction products. European Committee for Standardization.

ISO 21930:2017. Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products. International Organization for Standardization.

EN 50693:2019. Product category rules for life cycle assessments of electronic and electrical products and systems. European Committee for Standardization.

Ecoinvent v3, 2019. Allocation, cut-off by classification. Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021). eEPD v2021.09, background information for EPD generator tool system verification, LCA.no. Report number: 07.21. System verification report.

Philis et al., (2022). EPD generator for IBU PCR part B for luminaires, lamps, and components for luminaires, background information for EPD generator application and LCA data, LCA.no. Report number: 04.22. PCR verification report.

EPD Norway (2022). NPCR Part A: Construction products and services. The Norwegian EPD foundation. Version 2.0 published 24.03.2021.

IBU (2017). PCR part B for luminaires, lampes and components for luminaires. Institut Bauen und Umwelt e.V. Version 1.7, published 30.11.2017.

Life cycle inventory (LCI) report for MIRS67-600 (M) G2 2500 HF TW M20 FR/PC, Glamox, April 2024.

| | | |
|---|--|---|
|  epd-norway <small>Global Program Operator</small> | Program operator and publisher The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway | Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-norge.no |
|  | Owner of the declaration: Glamox AS Birger Hatlebakks veg 15, 6415 Molde | Phone: +47 97551574 e-mail: birger.holo@glamox.com web: https://www.glamox.com |
|  | Author of the Life Cycle Assessment LCA.no AS Dokka 6B, 1671 | Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no |
|  | Developer of EPD generator LCA.no AS Dokka 6B, 1671 Kråkerøy | Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no |
|  | ECO Platform ECO Portal | web: www.eco-platform.org web: ECO Portal |